

Technical data article: **O₂Zone**

Laboratory Test

<u>Description</u>	<u>Normative</u>	<u>Secured</u>
Flexing endurance Method:	DIN 53351	30,000 cycles without cracking
Colour fastness to light Method:	ISO 105 B02	> 5
Colour fastness to and fro rubbing: Method:	EN ISO 11640	Dry 500 > = 5 Wet 200 > = 4 Sweat 50 > = 4
Sweat Alkaline Solution	EN ISO 11641	Ph 4 - 5
Tear Strength:	DIN S3329	> 20N N/mm
Finish Adhesion Method:	EN ISO 11644	> 2.5 N/10mm
Determination of pH Difference figure (only for pH < 4) Method:	EN ISO 4045	3.72
Fire Rating and Flammability: Royal fulfills the following flammability requirements:	Ö-Norm B1, Tri, Q1; DIN EN 1021Teil 1+2; ISO 8191-1, BS 5852, California TB 117 (Draft 02/02)	Pass Pass
Care Instructions:	<ul style="list-style-type: none"> > Vacuum regularly with soft brush > Use a damp white cloth that is colourfast and wipe regularly > Do not use detergents, solvents, abrasives > Protect from direct sunlight and heat sources > Avoid sharp objects 	

WWW.NSWLEATHER.COM