

# Technical data article: **Casablanca**

## Laboratory Test

<u>Description</u>	<u>Normative</u>	<u>Secured</u>
Flexing endurance Method:	ISO 5402	>50,000 cycles
Colour fastness to light Method:	ISO 105 B02	> = 6 Blu Scale
Colour fastness to and fro rubbing: Method:	EN ISO 11640	Dry 500 > = 4 Wet 80 > = 4 Sweat 50 > = 4
Sweat Alkaline Solution	EN ISO 11641	Ph 8
Tear Strength, Single edge Tear Method:	EN ISO 3377-1	> = 20N
Finish Adhesion Method:	EN ISO 11644	> = 2.5 N/Cm
Determination of pH Difference figure (only for pH < 4) Method:	EN ISO 4045	> = 3.5 < = 0.7
Fire Rating:	AFRDI 146 EN ISO 1021-1 EN ISO 1021-2	Pass Pass
Care Instructions:	<ul style="list-style-type: none"> <li>&gt; Vacuum regularly with soft brush</li> <li>&gt; Use a damp white cloth that is colourfast and wipe regularly</li> <li>&gt; Do not use detergents, solvents, abrasives</li> <li>&gt; Protect from direct sunlight and heat sources</li> <li>&gt; Avoid sharp objects</li> </ul>	